

## **AMBUJET P800 D 20G**

Portable Suction Unit with auto recharge wall fixing 20G





The AMBUJET Wire P 800 D 20G suction device is the result of long term research investments. The collaboration between rescue operators and engineers has taken Jet to new levels of reliability, lightweight and at the same time being extremely user friendly as no other portable suction device has ever been. Jet has an unprecedented suction flow rate in its category - 32 L/min. and is the only device with the easy access for rapid battery substitution. The collection vase, being connected directly to the suction unit reduces the number of components and costs and is also quick and easy to insert. Jet is the first suction device in the world to be equipped with an integral protection frame in Polyethylene which protects from any kind of damage due to dropping, collisions, falls. A simply indestructible device as demonstrated by the UNI EN 1789 certification. The exceptional stability is obtained thanks to the position of the gravital centre in the area with the maximum distance from the external frame. In addition AMBUJET is supplied complete with a 20 g certified wall fixing system that is however very easily released by just pressing the button on the front.

Class IIa medical device Compliant with ISO 100079-1 ISO Class High flow / High vacuum Accessory

- SC75012E Jet Side Bag
- SC73017E 220V/12V power adapter

## **TECHNICAL DATA**

Dimensions 200x225x285 mm
Dimensions with hook 200 x 250 x h320 mm
Suction device weight 2,65 kg

Wall fixing hook weight 0,8 kg

Vacuum Range from 50 to 550 mmHg

Free flow Suction 32 I/min.
Noise level 70 dB
Fall protection Yes
Electrical connection

requirement 100-240 VAC 47-63 Hz 0,75 A max; 12VDC 33W max

Battery 12V DC Ni-MH
Battery use 30 min. ON, 30 min. OFF

Loading time 5 hours

Cable 12V No, integrated in hook

Power cable 220V No
Vase capacity 800 ml
Vase type Single use
Patient tube 1,80 mt
Temperature for use From 0°C

Temperature for use From 0°C to +45°C Temperature storage From -40°C to +70°C Humidity From 0 to 95%

Certified hook Yes EN 1789 (20G)
Auto power hook Yes
Grade IP IP 12

Shoulder strap Yes
Latex Free

SC75500D

AMBUJET P 800 D 20G

(E<sub>0434</sub>

UNCHECKED COPY - further revisions will be available on link http://support.spencer.it/en/pdf